



ORiNOCO AP-700

Technical Specifications



APPLICATIONS

- **Small and medium corporations**
Mobile access to improve employee, contractor and customer efficiency
- **Universities**
Flexible, immediate, mobile faculty and student connectivity in dorms, classrooms, libraries and campus quads
- **Hospitals and medical clinics**
Real time information system wide for better patient care and reduced errors
- **Local, state and federal agencies**
Fast access to information to serve constituencies better
- **Public hotspots**
Robust, secure, Wi-Fi connectivity for airports, convention centers, hotels

RADIO	Single Radio Access Point with integrated 802.11b/g/a radio mode; selectable by user	
DATA RATES SUPPORTED	802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps	
NETWORK STANDARD	IEEE 802.11b or IEEE 802.11g or IEEE 802.11a	
UPLINK	Autosensing 802.3 10/100BASE-T Ethernet	
FREQUENCY BAND	802.11b/g 2.412 to 2.462 GHz (FCC) 2.412 to 2.472 GHz (ETSI) 2.412 to 2.484 GHz (TELEC) 2.412 to 2.462 GHz (Taiwan) 2.412 to 2.462 GHz (Singapore) 2.412 to 2.462 GHz (S. Korea) 802.11a 5.15 to 5.35 GHz (FCC UNII 1 and UNII 2), 5.725 to 5.85 GHz (FCC UNII 3/ISM) 5.15 to 5.35 GHz and 5.47 to 5.725GHz (ETSI) 5.15 to 5.25 GHz (TELEC) 5.15 to 5.25 GHz and 5.725 to 5.825 GHz (Singapore) 5.25 to 5.35 GHz and 5.725 to 5.85GHz (Taiwan) 5.725 to 5.825GHz (S. Korea)	
NETWORK ARCHITECTURE TYPE	Infrastructure	
WIRELESS MEDIUM	802.11b or 802.11g: Direct sequence spread spectrum (DSSS); Orthogonal Frequency Division Multiplexing (OFDM) 802.11a: Orthogonal Frequency Division Multiplexing (OFDM)	
MEDIA ACCESS PROTOCOL	Carrier sense multiple access with collision avoidance (CSMA/CA)	
MODULATION	OFDM BPSK @ 6 and 9 Mbps QPSK @ 12 and 18 Mbps 16-QAM @ 24 and 36 Mbps 64-QAM @ 48 and 54 Mbps DSSS DBPSK @ 1 Mbps DQPSK @ 2 Mbps CCK @ 5.5 and 11 Mbps	
OPERATING CHANNELS	2.4 GHz Band 802.11b: ETSI: 13; Americas: 11; TELEC (Japan): 14 802.11g: ETSI: 13; Americas: 11; Japan (TELEC): 14 CCK, 13 OFDM 5 GHz Band FCC: 12 ETSI: 19 Japan (TELEC): 4 Singapore: 9 Taiwan: 8 S. Korea: 4	
NON-OVERLAPPING CHANNELS	Fifteen (FCC only)	
RECEIVE SENSITIVITY	802.11b 5.5 Mbps: -89 dBm 11 Mbps: -89 dBm 802.11g 5.5 Mbps: -89 dBm 11 Mbps: -89 dBm 36 Mbps: -82 dBm 54 Mbps: -76 dBm 802.11a 36 Mbps: -83 dBm 54 Mbps: -77 dBm	
AVAILABLE TRANSMIT POWER SETTINGS	802.11b 100 mW (20 dBm) 50 mW (17 dBm) 25 mW (14 dBm) 12.5 mW (11 dBm) Maximum power setting will vary according to individual country regulations.	

ORiNOCO AP-700 Technical Specifications

AVAILABLE TRANSMIT POWER SETTINGS (CONT'D)	802.11g	63 mW (18 dBm) 32 mW (15 dBm) 16 mW (12 dBm) 8 mW (9 dBm)
	Maximum power setting will vary according to individual country regulations.	
	802.11a	63 mW (18 dBm) 32 mW (15 dBm) 16 mW (12 dBm) 8 mW (9 dBm)
	Maximum power setting will vary according to individual country regulations.	
COMPLIANCE	Standards	
	Safety	UL 60950, CSA 22.2 No. 60950-00 IEC 60950 3rd Ed (1999)
	Radio Approvals	FCC Part 15.401-15.407 RSS-210 (Canada)
	Antenna Approvals	EN 301.893 EN300.328 EN301.489-1 EN301.489-17 EN50371 ARIB STD-T71, ARIB-STD 33, ARIB-STD 66 FCC 15.247 RSS-210
	EMI and Susceptibility (Class B)	FCC Part 15.107 ICES-003 (Canada)
	Security	AES and 802.11i WPA and WPA2 WEP and TKIP
	Network Standard	IEEE 802.11b IEEE 802.11g IEEE 802.11a
	Other	FCC Bulletin OET-65C WiFi Certification RSS-102 IEEE 802.3af
	SNMP COMPLIANCE	
	Orinoco; rfc1213; rfc1643; SNMPv2; 802.11i-D3; IANAifType-MIB; MIB802	
ANTENNA	2.4 GHz	
	Dual on-board antennas to support antenna and polarization diversity:	
		One 3dBi vertically polarized omni antenna, 360° horizontal and 40° vertical beamwidths
		One 2dBi horizontally polarized omni antenna, 360° horizontal and 30° vertical beamwidths
	Certified with	Proxim 1086-REA Proxim 1086-DA24-4 Proxim 1086-OA24-5 Proxim 1086-PA24-8.5 Proxim 1086-PA24-9.5
	5 GHz	
	Dual on-board antennas to support antenna and polarization diversity:	
		One 3dBi vertically polarized omni antenna, 360° horizontal and 40° vertical beamwidths
		One 2dBi horizontally polarized omni antenna, 360° horizontal and 30° vertical beamwidths
	Certified with	Proxim 1086-REA Proxim 1086-PA50-7
SECURITY ARCHITECTURE CLIENT AUTHENTICATION AND ENCRYPTION	2.4 and 5 GHz	
	Dual band (2.4 and 5GHz) external Range Extender Antenna for optimum antenna placement, 1086-REA	
	Authentication	802.11i/802.1X including support for PEAP, EAP-TLS, EAP-TTLS EAP-SIM, and other EAP methods that conform to RFC 3748[1] to yield mutual authentication and dynamic per-user, per-session encryption keys RADIUS-based MAC address MAC address control list
	Encryption	802.11i support for CCMP/AES keys of 128 bits (WPA2) TKIP encryption enhancements (for WEP) with key hashing (per-packet keying) and broadcast key rotation (WPA) Support for WEP keys of 64 and 128 bits

ORiNOCO AP-700 Technical Specifications

SECURITY ARCHITECTURE CLIENT AUTHENTICATION AND ENCRYPTION (CONT'D)	Message Authentication	802.11i AES message authentication with 128 bit keys TKIP with 128 bit Michael Message Integrity Check
INTRUSION DETECTION	Rogue AP and client detection Detect switch port of rogue access point when used in conjunction with Wavelink Mobile Manager Detect MIC intrusion attacks	
STATUS LEDS	Four indicators on the top panel indicate power, wireless traffic, Ethernet traffic, and error conditions	
REMOTE CONFIGURATION SUPPORT	DHCP, Telnet, HTTP, TFTP, Boot P, and SNMP	
LOCAL CONFIGURATION	RS-232 Serial port, DB9 Female	
DIMENSIONS	Packaged	11.375 x 9.25 x 2.75 inches (289 mm x 235 mm x 70mm)
	Unpackaged	7.8 x 4.75 x 1 inches (198 mm x 121 mm x 25 mm)
WEIGHT	Packaged weight	2.05 lbs (.92 kg)
	Unpackaged weight	.65 lbs (.29 kg) AP-only, .45 lbs (.20 kg) for power supply
ENVIRONMENTAL	Operating	0° to 55°C, 5-95% humidity non-condensing @ 5° to 55°C
	Storage	-20° to 85°C, 5-95% humidity non-condensing @ 5° to 85°C
PROCESSOR	220MHz MIPS 700 processor	
SYSTEM MEMORY	16 Mbytes RAM 8 Mbytes FLASH	
INPUT POWER REQUIREMENTS	90 to 240 VAC ±10% (power supply) 48 VDC ±10%(device)	
POWER DRAW	10 watts, RMS	
WARRANTY	One year	
WI-FI CERTIFICATION	View Wi-Fi Interoperability Certificate for ORiNOCO AP-700	
PART NUMBERS	8675-US	ORiNOCO AP-700 FCC-MU; with Middle and Upper Bands only for 802.11a, with antenna connectors
	8675-US2	ORiNOCO AP-700 FCC-LMU; with Lower, Middle and Upper Bands; no antenna connectors
	8675-AU	ORiNOCO AP-700 AU FCC-LMU; certified for Australia; Lower, Middle and Upper Bands for 802.11a; no antenna connectors
	8675-AU	ORiNOCO AP-700 AU FCC-LMU; certified for Australia; Lower, Middle and Upper Bands for 802.11a; includes external antenna connectors for 802.11b/g
	8675-AU2	ORiNOCO AP-700 AU FCC-MU; certified for Australia; Middle and Upper Bands for 802.11a; with antenna connectors
	8675-BR	ORiNOCO AP-700 BRAZIL-LU; certified for Brazil; with antenna connectors
	8675-JP	ORiNOCO AP-700 JP-L; certified for Japan; with antenna connectors
	8675-SG	ORiNOCO AP-700 UK SG-U; certified for Singapore; with antenna connectors
	8675-CN	ORiNOCO AP-700 CN-U; certified for China; with antenna connectors
	8675-SK	ORiNOCO AP-700 ASIA-L; certified for South Korea; with antenna connectors
	8675-TW	ORiNOCO AP-700 TW-MU; certified for Taiwan; with antenna connectors
	8675-EU	ORiNOCO AP-700 EU ETS-L; with Lower Band only for 802.11a, with antenna connectors
	8675-EU2	ORiNOCO AP-700 EU ETS-LM with Lower and Middle Bands for 802.11a, with antenna connectors; certified for Finland, Germany and Netherlands only
	8675-UK	ORiNOCO AP-700 UK ETSI-LM; with Lower and Middle bands, with antenna connectors
	Customers are responsible for verifying approval for use in their country. Not all regulatory domains have been approved.	



Proxim Corporation
935 Stewart Drive
Sunnyvale, California 94085

tel: 800.229.1630
tel: 408.731.2700
fax: 408.731.3675
www.proxim.com



¹ To achieve 802.11i security, the EAP method that is used must conform to both RFC 3748 and IETF draft-walker-ieee802-req-07 (Submitted as an Informational RFC). In RFC 3748, EAP- MD5-Challenge (Section 5.4), One-Time Password (Section 5.5) and Generic Token Card (Section 5.6), are non-compliant with the requirements specified in IETF draft-walker-ieee802-req-07 and thus do not support the 802.11i security claims when used with 802.11i.