

54M High Power Wireless Access Point

TL-WA5110G



High Power and receive sensitivity design to boost your signal coverage and link speed

Optimized performance for Ultra-Long-Distance wireless transmission

Power over Ethernet for flexible deployment



Description:


The TL-WA5110G 54M High Power Wireless Access Point is dedicated to Small Office/Home Office (SOHO) and long distance wireless network solutions. It integrates the functions of a Wireless Access Point, WISP Client, Firewall, and NAT-Router. It features high output power and high receive sensitivity can significantly extend the transmission range to reduce dead spots and to deliver a more stable wireless connection.

The TL-WA5110G provides three operation modes for multiple users to access the Internet: AP client router, AP router and AP. In AP client router mode, it works as a WISP CPE. In AP router mode, it can access the Internet via an ADSL/Cable Modem. In AP mode it can work in various modes, such as Access Point/Client/WDS Bridge/Repeater.

Specifications:

Standards	IEEE 802.11g IEEE 802.11b	
Interface	One 10/100M Auto-Sensing RJ45 Port(Auto MDI/MDIX), supporting Passive PoE	
Wireless Signal Rates With Automatic Fallback	11g:108/54/48/36/24/18/12/9/6 Mbps (Dynamic) 11b:11/5.5/3/2/1 Mbps (Dynamic)	
Frequency Range	2.4-2.4835GHz	
Wireless Transmit Power	Up to 20dBm	
Antenna	4dBi detachable Omni directional antenna	
Modulation Type	IEEE 802.11b: DQPSK, DBPSK, DSSS, and CCK IEEE 802.11g: BPSK, QPSK, 16QAM, 64QAM, OFDM	
Receiver Sensitivity	802.11g 54M: -75dBm±1dB 9M: -92dBm±1dB	802.11b 11M: -91dBm±1dB 1M: -95dBm±1dB
Power Supply Unit	Input: localized to country of sale Output: 12VDC / 1A linear PSU	
Certifications	CE, FCC	
Operating Temperature	-10°C~40°C (14°F~104°F)	
Storage Temperature	-40°C~70°C (-40°F~158°F)	
Relative Humidity	10% ~ 90%, non condensation	
Storage Humidity	5%~90% non-condensing	
Dimensions	6.5 × 4.2 × 1.1 in. (165 × 108 × 28mm)	

Diagram:



Features:

- Supports AP Client Router(WISP Mode), AP Router and AP operation mode.
- High output transmission power and reception sensitivity optimized.
- Supports Passive Power over Ethernet.
- Supports Wireless Distribution System (WDS).
- Distance Adjustment for long range transmission, up to 50km*.
- Supports Antenna Alignment.
- Supports Layer 2 User Isolation.
- Provides throughput monitor.
- Supports Ping Watch Dog.
- Supports Link Speed Test.
- Supports Remote Management.
- Supports PPPoE, Dynamic IP, Static IP Internet Access.
- Built-in NAT and DHCP server Supports Address Reservation.
- Provides 64/128/152-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK data security and TKIP/AES encryption, WLAN ACL (Access Control List).
- Supports configuration backup/restore and firmware upgrades.

* High gain directional antenna dependent

Package Contents:

- 54M High Power Wireless Access Point TL-WA5110G
- Power Adapter
- RJ-45 Ethernet Cable
- Quick Installation Guide
- Power Injector
- Resource CD

Related Products:

- 14dBi 2.4GHz Directional Antenna TL-ANT2414A
- 24dBi 2.4GHz Grid Parabolic Antenna TL-ANT2424B
- 8-port Unmanaged 10/100M Desktop Switch TL-SF1008D

Specifications are subject to change without notice. is a registered trademark of TP-LINK Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. No part of the specifications may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from TP-LINK Technologies Co., Ltd.